

Pocket-LEPTOSKOP®
Coating Thickness Measurement

Models 2018 NFe 2021 Fe 2026 Fe/NFe

KARL DEUTSCH

Do you want your coating thickness gauge to be flexibly usable together with excellent readability even at hard-to-access locations?

Then the new Pocket-LEPTOSKOP with its large illuminated flip display will exactly meet your requirements.

With the new generation of the Pocket-LEPTOSKOP gauges KARL DEUTSCH is setting the standard:

- · Convenient single hand operation: Switch-on and measure
- · Comfortable and quick. Already calibrated
- Large digits facilitate reading of the display
- · Reliable values in less than one second
- Easy menu guidance via 4 keys (foil keypad)
- · Clear understandable user guidance, comparable to a cellular phone
- · Rotate the contents of the large illuminated display simply by keystroke
- Integrated, spring-loaded probe
- Free language selection: German, English, French, Spanish, Italian, Swedish. More languages on request.

Optionally available for all Pocket-LEPTOSKOPs:

- Module "Statistics & Data Memory"
- Permits storage of up to 800 readings
- Statistics functions: Minimum, maximum, number of readings and mean value
- Keyboard lock, analog pointer display, graphical representation of readings
- Selectable limits and offset
- · PC software iCom for transfer of measured data to the PC and evaluation, storage and archiving of them.
- PC software "EasyExport" for the export of individual readings or whole data files into Windows programs.

Pocket-LEPTOSKOP 2018 NFe - for measurements of colour, lacquer, plastic, rubber, ceramic, insulation and galvanic coating on all non-magnetic metals like aluminium, copper, brass or certain high-grade steel (eddy current method -**DIN EN ISO 2360)**

Pocket-LEPTOSKOP 2021 Fe - for measurements of colour, lacquer, plastic, rubber, ceramic, insulation, galvanic or plated coating on iron and steel (magnetic inductive method -**DIN EN ISO 2178)**

Pocket-LEPTOSKOP 2026 Fe/NFe - the combined probe measures on all metallic substrates and will detect the substrate automatically



Statistics functions



Flip display: easy to read even when measuring overhead



Serial PC interface



Pocket-LEPTOSKOP with accessories

ordering data and scope of supply

| | Order No. |
|---|--------------|
| Instruments | |
| Pocket-LEPTOSKOP 2018 NFe | 2018.901 |
| Pocket-LEPTOSKOP 2021 Fe | 2021.901 |
| Pocket-LEPTOSKOP 2026 Fe/NFe | 2026.901 |
| Scope of supply: gauge with battery, calil | |
| reference block, instruction manual, quality certificate, | |
| equipment case | ,, |
| - 1 T | |
| Extended functions | |
| Module "Statistics and Data Memo | |
| for 2018/2021/2026 | 2910.001 |
| Accessories for data transfer | |
| Package "iCom" | 2018.912 |
| Scope of delivery: Module "Statistics and Da | ata Memory". |
| PC and printer cable, PC software "iCom" | |
| | 2018.913 |
| Package "EasyExport" | |
| Scope of delivery: Module "Statistics and Da | |
| PC and printer cable, PC software "EasyE | xport" |
| Accessories | |
| Mohile Thermal Printer | |

(battery-powered) PC and printer cable (RS232)

PC cable (USB, incl. drivers CD)

25 mm x 16 mm approx., illuminated Measuring ranges NFe (2018/2026): 0..1200 µm (47 mils) Fe (2021/2026): 0..3000 um (120 mils) Calibration Zero and multi-point calibration with mean calculation for uneven surfaces or standard calibration ex works Measurement uncertainty For coatings < 100 μm : 1% \pm 1.5 μm (after two point calibration on For coatings 100..1200 μm : 1 to 3 % \pm 1 μm ST 52 / AIMaSi0.5) For coatings > 1200 μm : 3 to 5 % \pm 1 μm Interface RS 232 Measurement units To be selected from um. mm. inch and mil **Battery operation** 1 alkali/manganese battery, 70 hrs life-time if illumination is off Indication of battery capacity Visually by symbol in the display and alarm tone Size/weight 46 mm x 95 mm x 16 mm, 70 g (2.6 oz)

Technical Data Pocket-LEPTOSKOP 2018 / 2021 / 2026

KARL DEUTSCH Prüf- und Messgerätebau GmbH + Co KG Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany Phone (+49 -202) 71 92 - 0 · Fax (+49 -202) 71 49 32 info@karldeutsch.de · www.karldeutsch.de

DIN EN ISO 9001 certified

Leaflet P 20 Pocket E · Subject to change without notice · Printed in Germany 05/15 · 7499.P20PL.EN.0515