



DEUTROPULS SW 2000

DEUTROPULS SW 1000

### Transportable Current Flow Units

- for mobile operation
- for multiple use
- high, infinitely variable current
- current indicator

## Technical data

	<b>DEUTROPULS SW 1000</b> Alternating Current	<b>DEUTROPULS SW 2000</b> Alternating Current	<b>DEUTROPULS SW 3000</b> Alternating Current	<b>DEUTROPULS SW 1000 G</b> Direct Current*
<b>Ordering no.</b>	3454.051	3454.052	3454.053	3454.151
<b>Inspection data</b>				
Current, effective (A)	1000	2000	2890	1000 770*
Current control	infinitely variable	infinitely variable	infinitely variable	infinitely variable
Open-circuit voltage (V)	2,8	5	7,5	2,8
Relative duty cycle	30%	30%	30%	30%
Demagnetization	included	included	included	-
<b>Operational data</b>				
Mains supply	230 V 50/60 Hz	400 V 50/60 Hz	400 V 50/60 Hz	230 V 50/60 Hz
Power consumption (kW)	3	8,7	22	5,5
<b>Dimensions</b>				
L x W x H (mm)	295 x 275 x 255	470 x 335 x 265	470 x 355 x 305	510 x 320 x 275
Weight (kg)	25	41	59	32

\*) half-wave rectified

### Accessories

- Security foot switch
- Flexible high current cables (2,5 m and 5 m with 70 mm<sup>2</sup> or 120 mm<sup>2</sup>)
- Contact magnets (Ø 40 mm or Ø 50 mm)

Find more accessories in our leaflet P 38 and our FLUXA detection media in P 90.

Please contact also our web-site: [www.karldeutsch.de](http://www.karldeutsch.de)

